



JB/T2300-1999
110 serie

Number	Basic Type	Dimensions			Installation hole size				Structure size				Weight Reference (KG)	
	Toothless DL mm	D mm	d mm	H mm	D ₁ mm	D ₂ mm	n	Φ mm	n ₁	D ₃ mm	d ₁ mm	H ₁ mm		h mm
1	110.25.500	602	398	75	566	434	20	18	4	498	502	65	10	77
2	110.25.560	662	458	75	626	494	20	18	4	558	562	65	10	87
3	110.25.630	732	528	75	696	564	24	18	4	628	632	65	10	95
4	110.25.710	812	608	75	776	644	24	18	4	708	712	65	10	111
5	110.28.800	922	678	82	878	722	30	22	6	798	802	72	10	167
6	110.28.900	1022	778	82	978	822	30	22	6	898	902	72	10	186
7	110.28.1000	1122	878	82	1078	922	36	22	6	998	1002	72	10	204
8	110.28.1120	1242	988	82	1198	1042	36	22	6	1118	1122	72	10	233
9	110.32.1250	1390	1110	91	1137	1163	40	26	5	1248	1252	81	10	337
10	110.32.1400	1540	1260	91	1487	1313	40	26	5	1398	1402	81	10	369
11	110.32.1600	1740	1460	91	1678	1513	45	26	5	1598	1602	81	10	425
12	110.32.1800	1940	1660	91	1887	1713	45	26	5	1798	1802	81	10	525
13	110.40.2000	2178	1825	112	2110	1891	48	33	8	1997	2003	100	12	815
14	110.40.2240	2418	2065	112	2350	2131	48	33	8	2237	2243	100	12	944
15	110.40.2500	2678	2325	112	2610	2391	56	33	8	2497	2503	100	12	1026
16	110.40.2800	2978	2625	112	2910	2691	56	33	8	2797	2803	100	12	1375
17	110.50.3150	3376	2922	134	3286	3014	56	45	8	3147	3153	122	12	2097
18	110.50.3550	3776	3322	134	3686	3414	56	45	8	3547	3553	122	12	2470
19	110.50.4000	4226	3772	134	4136	3864	60	45	10	3997	4003	122	12	2800
20	110.50.4500	4726	4272	134	4636	4364	60	45	10	4497	4503	122	12	3100